

model: 3131 eff



- **3³/₄-digit; 300 A AC/DC; True rms**
- **3 ³/₄ digit, 13 mm LCD Display, max. indication: 3999**
- **10 mA resolution**
- **ACA/DCA Measurements up to 300 A**
- **True rms measurements**
- **Continuity beeper**
- **Auto-Zeroing key for DCA**
- **Data hold and max. hold function**
- **Auto ranging**
- **Auto power off selectable**
- **max. conductor size: 22 mm**
- **Safety: IEC-1010-1; CAT II 600 V**
- **Accessories: Carrying case, test lead, battery and manual**

Functions

DCV 400 mV/4/40/400/600 V; ± 0,5% + 2 dgt. - 0,1 mV	Overload protection 600 Vrms
ACV 400 mV/4/40/400/600 V; ± 1,5% + 5 dgt. - 0,1 mV	Overload protection 600Vrms
DCA 40/300 A; ± 1% + 2 dgt. - 10 mA	Overload protection 400 Arms
ACA 40/300 A; ± 1% + 3 dgt. - 10 mA	Overload protection 400 Arms
Ohm 400 Ω/4/40/400 kΩ/4/40 MΩ; ±0,9% + 2 dgt. - 0,1 Ω	Overload protection 600 Vrms
Battery 2 x 1,5 V (AAA)	Dimensions (WxHxD) 66 x 192 x 27 mm
Weight 205 g	