

PeakTech 3720



3 ³/₄-digit

Digital multimeter with automatic range selection and 3³/₄-digit display, 3200 and 33 segment analogue bargraph. Measurements of DC/AC V, DC/AC A, resistance, frequency, temperature, transistor, diode and continuity are possible. The high accuracy ruggedized construction, reliability are some main features for using in laboratories, service, R+D and electrical field.

- 21 mm LCD-display
- Auto power off
- Auto ranging
- Data- and range hold function
- Transistor hFE-test
- Continuity- and Diode-test
- Buzzer
- Safety: IEC-1010-1; CAT II 1000 V/CAT III 600 V
- Accessories: Holster, test leads, battery, type-K-thermocouple probe, operation manual

DCV

300 mV/3/30/300/1000 V; $\pm 0,5\%$ + 2 dgt. - 100 μ V

ACV

3/30/300/750 V; $\pm 1,2\%$ + 5 dgt. - 1 mV

DCA

300 μ A/3/30/300 mA/10 A; $\pm 1,2\%$ + 2 dgt. - 100 nA

ACA

300 μ A/3/30/300 mA/10 A; $\pm 2\%$ + 5 dgt. - 100 nA

Ohm

300 Ω /3/30/300 k Ω /3/30 M Ω ; $\pm 1,2\%$ + 2 dgt. - 100m Ω

Freq.

300 kHz; $\pm 3\%$ + 5 dgt. - 100 Hz

Temp.

-40 ... +1000°C; $\pm 2\%$ + 5 dgt. -1°C

Power supply

2 x 1,5 V AAA

Dimensions

(W x H x D) 91 x 187 x 34 mm

Weight

350 g

Contact.

Telonic Instruments Ltd

Tel: 0118 9786911